

# ELIT TD-100-125ALL

Two-pole distribution block, 100/125 A, 1-line side and 14 load side connections

## Technical description

Two-pole distribution block 100/125ALL. Mounting on DIN rail or mounting plate. Easy connection with input terminal separated from output terminals. Covering of transparent blue plastic. Self-extinguishing.

Note! The image is for illustration only. The product has two poles.

## Advantages:

In accordance with RoHS

Halogen-free

Minimal space for maximum effect

Protective cover and insulating screens are transparent

Insulating screen between each row

Simple and secure connections

Easily clips onto DIN rail or mounts on panel with screws

Solid rails provide reliability

Input separated from outputs

Strong mechanical mounting

Neutral rail available

Complies with EN 45545 and receives an HL3 classification for chapter R23 and HL2 classification for chapter R22



Product name/ Art.nr/ GTIN	ELIT TD-100-125ALL/ 20400055/ 7070811206727
According to:	---
Height	90 Millimetre
Width	182 Millimetre
Depth	50 Millimetre
Max. rated current	125 Ampere
Number of poles	2
Conductor cross section flexible (fine-strand) with cable end sleeve	10 - 35 Square millimetre
Conductor cross section solid (solid, stranded)	10 - 25 Square millimetre
Number of clamp positions per pole	7