

ELIT UDF-250A

Distribution Block UDF 250A

Technical description

Single-pole distribution block. Visible confirmation of the cable connection through a transparent cover. The cover can be removed or flipped out. Halogen-free. Touch protection: IP20. Modular. Self-extinguishing plastic. Tinned copper blocks. Electrical connection between one or more blocks via cable or rail. For mounting on DIN rail or secured with mounting brackets. Made according to IEC 60947-7-1.

Advantages:

In accordance with RoHS
 Halogen-free
 Tinned copper or aluminum block allows direct connection of copper or aluminum conductors, or using a sleeve
 The screw terminal cover is hinged and removable
 The design allows for visual inspection of the conductor and confirmation of connection
 Modular click blocks for building multipole power blocks
 Easily clips onto DIN rail or mounts on panel with screws
 95% filling degree
 Complies with EN 45545 and receives an HL3 classification for chapter R23 and HL2 classification for chapter R22



Product name/ Art.nr/ GTIN	ELIT UDF-250A/ 20400068/ 7070811207908
According to:	---
Height	79 Millimetre
Width	29 Millimetre
Depth	46 Millimetre
Max. rated current	250 Ampere
Number of poles	1
Conductor cross section flexible (fine-strand) with cable end sleeve	16 - 70 Square millimetre
Conductor cross section solid (solid, stranded)	2,5 - 16 Square millimetre
Number of clamp positions per pole	6