




**ELIT**

## Freestanding air termination pole 3m w/HVC




Freestanding air-termination set 3.0m w/HVC flange, stand and concrete foundations

### Technical description

Freestanding air-termination pole set for HVC conductor with stand and concrete foundation.  
 Material and dimensions of standpipe: stainless A2 steel, Ø 42 mm, 0.9 m length.  
 Material and dimensions of insulating support: Glass fiber reinforced plastic, Ø 48 mm, 1.7 m length.  
 Material and dimensions of air-termination rod: Aluminum, Ø 10 mm, length 400 mm.  
 Concrete foundation: 12 kg, 650 x 650 mm.  
 Wind speed with a static safety factor of 1.0: 150 km/h  
 Wind speed with a static safety factor of 1.5: 123 km/h

### Advantages:

Freestanding air-termination set w/stand and base  
 Specially designed for up to 4 x HVC conductors  
 Manufactured in accordance with EN 62561-2, IEC/TS 62561-8



Product name/ Art.nr/ GTIN	ELIT FRITT-LOFSETT-3M-HVCFLENS/ 40150184/ 7070810034437
According to:	DIN EN 62561-2, DIN IEC/TS 62561-8
Length	3000 Millimetre
Diameter	48 - 10 Millimetre
Model	Interception rod with tripod
Material	Aluminium/stainless steel 304 (V2A)
Surface protection	Hot-dip galvanized
Connection	Round conductor