



ELIT

Freestanding air-termination set 5m w/HVC

Freestanding air-termination set 5.0m w/HVC flange, stand and concrete foundations



Technical description

Freestanding air-termination set for up to 4 x HVC conductors with stand and concrete foundations.
 Material and dimensions of mast: stainless A2-steel, Ø 42 mm, 0.9 m length.
 Material and dimensions of insulated support: Glass fiber reinforced plastic, Ø 48 mm, 1.7 m length.
 Material and dimensions of arrester tip: Aluminum, Ø 32/22/10 mm, 2,3 m length.
 Wind speed with a static safety factor of 1.0: 137 km/h
 Wind speed with a static safety factor of 1.5: 112 km/h

Advantages:

Freestanding air-termination set w/stand and base
 Specially designed for up to 4 x HVC conductors
 Manufactured in accordance with EN 62561-2, IEC/TS 62561-8

Necessary set-up area:



Product name/ Art.nr/ GTIN	ELIT FLOPSETT5MEKSHVC/ 40150195/ 7070810035304
According to:	EN IEC 62561-2, EN IEC 62561-8
Length	5000 Millimetre
Diameter	48 - 10 Millimetre
Model	Interception rod with tripod
Material	Aluminium/stainless steel 304 (V2A)
Surface protection	Hot-dip galvanized
Connection	Round conductor