




# ELIT

## Freestanding air termination pole 4m w/HVC




Freestanding 2-part air-termination set 4.0m w/HVC flange, stand and concrete foundations

### Technical description

Freestanding 2-part air-termination set for HVC conductors with stand and concrete foundations.  
 Material and dimensions of mast: stainless steel V2A, Ø 42 mm, 1.9 m length.  
 Material and dimensions of insulated support: Glass fiber reinforced plastic, Ø 48 mm, 1.7 m length.  
 Material and dimensions of arrester tip: Aluminum, Ø 10 mm, 400 mm length.  
 Concrete foundations: 3 x 16 kg with footprint 1285 x 1235 mm.  
 Wind speed with a static safety factor of 1.0: 145 km/h  
 Wind speed with a static safety factor of 1.5: 118 km/h

### Advantages:

Freestanding 2-piece air-termination set w/stand and base  
 Specially designed for up to 4 x HVC conductors  
 Manufactured in accordance with EN 62561-2, IEC/TS 62561-8



Product name/ Art.nr/ GTIN	ELIT FRITT-LOFSETT-4M-HVCFLENS/ 40150204/ 7070810036585
According to:	EN 62561-2, IEC/TS 62561-8
Length	4000 Millimetre
Diameter	48 - 10 Millimetre
Model	Interception rod with tripod
Material	Aluminium/stainless steel 304 (V2A)
Surface protection	Hot-dip galvanized
Connection	Round conductor
High-voltage-proof insulated model	Yes