

ELIT

Down conductor mount for HVC85 without

HVC-mounting clamp for fixing the HVC-conductor

Technical description

Down conductor clamp / Turnbuckle in stainless steel for mounting HVC-85 down conductor to pipes and masts.
Comes without fastening strap (fastening strap: 22 mm)
Material in pipe clamp: stainless steel
Material in spacer: aluminum
Material in conductor clamp: stainless steel
Fit in conductor clamp: Ø 28 mm (HVC-85 down conductor)
Distance to down conductor: 100 mm
Manufactured in accordance with EN62561-4.

Advantages:

Can be attached to a wide range of different mast diameters
Made of stainless steel and provides 100 mm distance to down conductor
Quick and easy to attach and for universal use
Manufactured according to EN62561-4



Product name/ Art.nr/ GTIN	ELIT NLF-HV85-100mm-FB22mm-A2/ 40170077/ 7070810036301
According to:	EN 62561-4
Mounting type conductor	With screw clamp
Suitable for diameter round conductor	28 - 28 Millimetre
Material of holder	Stainless steel 304 (V2A)
Mounting type holder	Tension band
Material of carrier	Stainless steel 304 (V2A)
Material of saddle clamp	Stainless steel 304 (V2A)
Material base part	Stainless steel 304 (V2A)
Pipe chucking range	20 - 500 Millimetre
Wall distance	100 - 100 Millimetre
Assembly height conductor holder	100 Millimetre