

ELIT

HVC-85 - Tape pipe clamp up to \varnothing 300 mm -


Down conductor attachment with up to \varnothing 300mm fastening strap for attaching high-voltage cable HVC-85

Technical description

Down conductor clamp / Pipe clamp with tension band up to \varnothing 300mm with conductor clamp for HVC-85 conductor for mounting on masts and pipes.
 Material of pipe clamp: stainless steel A2
 Tension strap (length x thickness): 22 x 0.4 mm for pipes up to \varnothing 300 mm
 Material of spacer: aluminum
 Material of conductor clamp: stainless steel A2
 Fit in conductor clamp: \varnothing 28 mm
 Height of conductor guide: 100 mm
 Manufactured in accordance with EN 62561-4.

Advantages:

Can be attached to a wide range of masts and pipes with a diameter of up to 300mm
 Made of A2 stainless steel and provides 100mm distance to the surface
 Quick and easy to attach and for universal use
 Manufactured according to EN 62561-4



Product name/ Art.nr/ GTIN	ELIT NLF-HV85-100mm-FB22mm- \varnothing 300mm-A2/ 40170078/ 7070810036318
According to:	DIN EN 62561-4
Mounting type conductor	With screw clamp
Suitable for diameter round conductor	28 - 28 Millimetre
Material of holder	Stainless steel 304 (V2A)
Mounting type holder	Tension band
Material of carrier	Stainless steel 304 (V2A)
Material of saddle clamp	Stainless steel 304 (V2A)
Material base part	Stainless steel 304 (V2A)
Pipe chucking range	30 - 300 Millimetre
Wall distance	100 - 100 Millimetre
Assembly height conductor holder	141 Millimetre