



ELIT HRD 150-SG-6/8-35

Press Seal \varnothing 150mm A2 6x \varnothing 8-35mm

Press seal for core drilled hole with diameter \varnothing 150mm. For 6 cables \varnothing 8-35mm.

Technical description

Press seal for core drilled hole or wall bracket. Made of EPD rubber with stainless steel flanges. The seal is easily installed into the hole and rubber slats are removed in the seal according to the diameter of the cable to be passed through.

Tighten with a torque wrench according to the included installation instructions. The product provides a water and gas tight penetration that also prevents pests from entering the building. Gas-tight, waterproof and radon-proof.

Material:

Pressure plates, screws, nuts and washers: stainless steel V2A (AISI 304L), (V4A (AISI 316L) on request)

Rubber: EPDM

The product includes:

6 x blind plugs

1 x lubricant



Advantages:

Quick and easy to install even where cables are already routed through

Provides water and gas tight penetration and prevents access for pests

Segmented solution that allows easy adaptation to cable diameter

Product name/ Art.nr/ GTIN	ELIT HRD 150-SG-6/8-35/ 60200008/ 7070810038763
According to:	Water exposure class DIN 18533: W1-E, W2.1-E and W2.2-E. Waterproof concrete stress class 1 and 2. Pressure test performed with test pressure 2.5 bar(g), >72 hours, test medium: water/air, ambient temperature 22 °C. Neither leakage nor deformation could be identified after the pressure test.
Model	Closed
Cable entry	Round
Number of cables	0 - 6
Suitable for cable diameter	8 - 35 Millimetre
Bore diameter	150 Millimetre
For wall thickness	60 - Millimetre
Total length	60 Millimetre
Material	Rubber
Material quality	Ethylene-propylene diene monomer rubber (EPDM)
Surface protection	Untreated
Colour	Black
Gastight	Yes
Watertight	Yes