



ELIT HRK200-SSG 3x40-72

Press seal \varnothing 200mm A4 3x40-72mm

Press seal \varnothing 200 mm with super segmented ring technology and polymer press plates - 3 x \varnothing 40-72mm

Technical description

Press seal for sealing cables in core holes or sleeves.
Split design for sealing newly installed cables or cables that have already been installed.

Wall sleeve/core hole: \varnothing 200mm
Sealing width: 40 mm
Openings: 3
Diameter of pipes/cables: \varnothing 40 - 72 mm

Material:
Press plates: glass fiber reinforced polyamide
Rubber: EPDM
Screws and nuts: acid-resistant A4 steel (AISI 316L)

Advantages:

Segmentation technology for individual adaptation to cable diameters on site
For sealing newly installed cables or cables that have already been installed
Gas-tight, water-tight and with radon barrier
Includes: Blind plug (for multiple cable entries), 1 knife, 1 lubricant stick



Product name/ Art.nr/ GTIN	ELIT HRK200-SSG 3x40-72 b40 PAGF/A4/EPDM/ 60200011/ 7070810040971
According to:	Water exposure class DIN 18533: W1-E, W2.1-E and W2.2-E. Waterproof concrete stress class 1 and 2. Pressure test performed with test pressure 2.5 bar(g), >72 hours, test medium: water/air, ambient temperature 22 °C. Neither leakage nor deformation could be identified after the pressure test.
Suitable for cable diameter	40 - 72 Millimetre
Outer diameter of ring	200 Millimetre
Height	200 Millimetre