

ELIT

Eombo Torx-Slot TX25-S72

Fold clamp galvanized steel Ø8 - 10mm

ELIT Saddle clamp galvanized steel Ø8 - 10mm

Technical description

Saddle clamp in accordance with EN 62561-1, with mounting bracket for secure connection to sheet and steel structures. Clamping range up to 5 mm, and supplied with 4 pcs M6 cylinder head screws. Conductor, Ø8-10 mm, can be installed lengthwise or crosswise. The material is hot-dip galvanized (immersed in molten zinc), providing excellent resistance to corrosion and rust.


Advantages:

Saddle clamp in accordance with mounting bracket for secure connection to sheet and steel structures

Clamping range up to 5 mm, and supplied with 4 pcs M6 cylinder head screws Conductor, \emptyset 810 mm, can be installed lengthwise or crosswise

The material is hot-dip galvanized (immersed in molten zinc), providing excellent resistance to corrosion and rust





Product name/ Art.nr/ GTIN	ELIT FALS-KLEM-GALV-Ø8-10mm/ 40170030/ 7070811203993
According to:	EN 62561-1
Mounting type conductor	With screw clamp
Suitable for diameter round conductor	8 - 10 Millimetre
Material of holder	Thermo galvanized steel/die-cast zinc
Mounting type holder	Other
Material of carrier	Steel galvanised
Material of saddle clamp	Steel galvanised
Material base part	Steel galvanised
Thread size (metric)	10
Assembly height conductor holder	10 Millimetre